

Odvrtlač pneumatski, kompozitni, prihvat 3/4"

1573



Profili



Opis proizvoda

- 5.500 o/min u slobodnom hodu
- max. obrtni moment: 2034 Nm
- max. obrtni moment pri odvijanju 3254 Nm
- preporučeni pritisak dovoda vazduha: 6,2 bar
- potrošnja komprimovanog vazduha: 198 l/min
- priključak za vazduh: 3/8"

- nivo buke: 93 dB(A)
- za vijke do M30

Prednosti:


- kompozitno kućište
- dvostruki udarni mehanizam TwinHammer
- laka i brza promena smera jednom rukom
- kompaktan i snažan
- sa regulatorom za 3 različite brzine zavrtnanja/odvrtanja





Upotreba:

- auto-industrija
- avio-industrija
- poljoprivredna mehanizacija
- teška industrija
- veće građevinske mašine
- brodogradnja
- individualna montaža

VAŽNO!

- UVEK koristite Uniorove IMPACT nasadne ključeve i pribor



		L	A	B		
627571	3/4"	220	88	217	2034	3764

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Upotreba (slike)



Slika (slike)



Dodatna oprema



Spojnica muška



Spojnica ženska



Priprema grupa za pneumatski alat 3/4"



Crevo spiralno za vazduh

Pravilna upotreba



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.



- Always disconnect tools not in use from the air supply.

- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.